



FOTON

TRUCK AHEAD OF THE COMPETITION



GTL-AMT_{6X4}
TRACTOR HEAD



Fuel Economy | Powerful Engine | Excellent Load Carrier

SPECIFICATION | FOTON GTL AMT 6X4 Tractor Head

BASIC INFORMATION	Function	Tractor head
	Drive Style	6x4
	Steering Wheel Position	Left hand
	Platform	GTL-AMT
	Vehicle Model	BJ4259SMFKB-AX
COMPLETE VEHICLE DIMENSION PARAMETERS	Wheelbase (mm)	3300+1350
	Long(mm)	7000
	Width(mm)	2500
	Height(mm)	3150
COMPLETE VEHICLE MASS PARAMETER	Chassis Kerb Weight(kg)	10435
	GCW(t)	90
CABIN	Body Type	Flat roof, all welded steel cab, 4-points spring suspension cab, manual hydraulic cab tilting, adjustable driver's seat(pneumatic seat), seatbelt for driver and co-driver, electric rear-view mirrors and windows, electric heated rearview mirror,central locking, MP3+Radio+USB
	Carrying Number	2 seats + 1 bunk
ENGINE	Engine Model	ISGe3-430
	Engine Type	Inline six-cylinder, four-stroke, water cooled, turbocharged, intercooled,direct injection, common rail diesel engine
	Displacement (cc)	11,800
	Max Power (kw/ps/rpm)	316/430/1900
	Max Torque (Nm/rpm)	2000/1000-1400
	Engine Brand	CUMMINS
	Emission	Euro III
CLUTCH	Clutch Type	Single, dry type diaphragm spring
	Plate Diameter(mm)	φ430
	Operating System	Automatic electric control

GEARBOX	Gearbox Model	12TX2420TD
	Gearbox Type	AMT (Automated Mechanical Transmission)
	Gearbox Brand	ZF
	Numbers of Gears	12 Forward and 2 Reverse
	PTO	Standard
BRAKE	Service Brake	Dual circuits pneumatic brake
	Parking Brake	Energy-accumulating spring air cut-off brake
	Auxiliary Brake	Engine brake
SUSPENSION	Front Suspension/ Leaf Spring Number	Longitudinal leaf spring with dual acting telescopic shock absorbers and anti-roll bar, 9 pieces
	Rear Suspension/ Leaf Spring Number	Longitudinal leaf spring with balance suspension, 12 pieces
FRONT AXLE	Capacity(kg)	9000
	Front Axle Brake Type	Drum brakes
REAR AXLE	Type	Double reduction(central reduction and hub reduction), tandem axle with differential locks between wheels and axles
	Capacity(kg)	2 x 16000
	Rear Axle Brake Type	Drum brakes
TYRE	Tyre Size	Standard:315/80R22.5 Optional:13R22.5
	Numbers of Tyres	10+1
STEERING	Type	Hydraulic steering with power assistance
	Steering Wheel	Adjustable
FUEL TANK	Type	Aluminum fuel tank with lockable cap
	Capacity	700L
ELECTRICAL SYSTEM	Rated Voltage	24V
	Battery	2x12V-165Ah
OTHER CONFIGURATION	ABS+ASR	Standard
	A/C	Standard
	Cruise	Standard
	Fifth Wheel	90#(3.5")
	ADR	Optional



ACCRA, Graphic Road
Head office
South Industrial Area.
P. O. Box 5216, Accra
Tel: +233 (556) 644 300
+233 (244) 342 430

TEMA,
Cocoa Processing Road
P. O. Box 199, Tema.
Tel: +233 (593) 872 297

TAMALE,
P. O. Box TL Tamale,
Kumasi Road.
Tel: +233 (593) 804 355

KUMASI,
P. O. Box 6015 Kumasi
Prempeh 1 Street Adum.
Tel: +233 (203) 300 762

TAKORADI,
P. O. Box MC 257, Paa
Grant Avenue. Takoradi.
Tel: +233 (554) 391 153