



FOTON

LIGHT DUTY TRUCK

NOW AT JAPAN MOTORS



AUMARK

**3 TON PAY LOAD
SINGLE CABIN**



JAPAN MOTORS
Driven by Excellence

Hotline: 0244 342 430

- Accra: 0302 682220
- Tema: 0303 204169
- Takoradi: 0312 031110

www.japanmotors.com

SPECIFICATION

Aumark TX Specifications		
Cabin		Single row seat tiltable
DIMENSION	Overall dimensions (LxWx H)mm	5995X1900X2260
	Inner dimensions of cargo body (LxWx H)mm	4230x1810x380
	Driving type	4x2
	Wheelbase (mm)	3360
	wheel track (front/rear) (mm)	1
	Min ground clearance	≥181
WEIGHT	Curb weight (kg)	2510
	Rated payload (kg)	3800
	Person in cab	2
	Gross vehicle weight (kg)	6310
PERFORMANCE	Max speed (km/h)	95
	Max slope of climb (%)	≥30
	Fuel consumption (L/100km)	≤12
	Min turning diameter (m)	≤14.5
ENGINE	Model	BJ493ZLQV1(EURO III)
	Type	Four cylinder, in-line,turbocharging, middle cooling
	Displacement (L)	2.771
	Rated Power (kw/ rpm)	76/3600
	Rated torque (N.m/rpm)	225/2200
GEARBOX	Model	5-26
	Speed ratio	1:5.594, i2:2.814, i3:1.660, i4:1.000, i5:0.794, iR:5.234
CLUTCH	Type	single disc, dry type, diaphrag spring; φ 250x φ 160
AXLE	Type/Main reducer ratio	Whole banjo type type, Spread ratio/6.142, use 4tons rear axle
SUSPENSION	Front suspension/leaf spring number	non-independent suspension, leaf spring 7
	Rear suspension/leaf spring number	leaf spring non-independent suspension, with auxilliary leaf spring, 5 + 4
STEERING GEAR	Type	Mechanical circular ball
BRAKING SYSTEM	Service brake	Front disc,rear drum(hydraulic dual circuits)
	Parking brake	Central drum brake
	Auxilliary brake	Exhaust brake
WHEELS AND TYRE SIZE		6+1 /7.00r16
ELECTRIC DEVICE	Rated voltage	12V
	Battery	80Ah
FUEL TANK (L)		120 (Aluminium)
BASIC EQUIPMENT		Silicon oil clutch fan, Rivet frame, Adjustable steering wheel, Hydraulic operation with clutch booster, central drum brake, exhaust brake, power steering, radio
OPTIONAL		Air Conditioner

- Silver Star Tower: 0302 768849-51
- Kumasi: 03220 30200
- Tamale: 03720 22125



FOTON