



INCREDIBLE **POWER** FOR DUTY

The **AUMAN GTL 6X4** Tipper Truck



Fuel Economy | Powerful Engine | 20m³ Tipper Bucket

SPECIFICATION | FOTON Auman 6X4 Tipper Truck

Basic Information	Function	Tipper truck
	Drive Style	6x4
	Steering Wheel Position	Left hand
Complete Vehicle Dimension Parameters	Wheelbase (mm)	3825 +1350
	Long (mm)	8400
	Width (mm)	2550
	Height (mm)	3400
Complete Vehicle Mass Parameter	GVW (kg)	55000
	Payload (kg)	40000
Cabin	Body Type	Flat roof, all welded steel cab, 2-points spring suspension cab, manual hydraulic cab tilting, adjustable driver's seat (pneumatic seat), seatbelt for driver and co-driver, manual rear-view mirrors and electric windows, central locking, MP3+Radio+USB
	Carrying Number	2 seats + 1 bunk
Engine	Engine Model	ISG-380
	Engine Type	Inline six-cylinder, four-stroke, water cooled, turbocharged, intercooled, direct injection, common rail diesel engine
	Displacement (cc)	10,800
	Max Power (kw/ps/rpm)	279 / 380 / 1900
	Max Torque (Nm/rpm)	1800 / 1000 - 1400
	Engine Brand	CUMMINS
	Emission	Euro III
	Clutch	Clutch Type
Plate Diameter(mm)		φ430
Operating System		Hydraulic control with air pressure assistance
Gearbox Brake	Gearbox Type	MT
	Numbers of Gears	12 Forward and 2 Reverse
	PTO	√
	Service Brake	Dual circuits pneumatic brake
	Parking Brake	Energy-accumulating spring air cut-off brake
	Auxiliary Brake	Engine brake

Suspension	Front Suspension / Leaf Spring Number	Longitudinal leaf spring with dual acting telescopic shock absorbers and anti-roll bar, 10 pieces
	Rear Suspension / Leaf Spring Number	Longitudinal leaf spring with balance suspension, 12 pieces
Front Axle	Capacity (kg)	9000
	Front Axle Brake Type	Drum brakes
Rear Axle	Type	Double reduction (central reduction and hub reduction), tandem axle with differential locks between wheels and axles
	Capacity (kg)	2 x 16000
	Rear Axle Brake Type	Drum brakes
Tyre	Tyre Size	13 R 22.5
	Numbers of Tyres	10
Steering	Type	Hydraulic control with air pressure assistance
	Steering Wheel Position	Adjustable
Fuel Tank	Type	Aluminum fuel tank with lockable cap
	Capacity (Liters)	350 L
Electrical System	Rated Voltage	24 V
	Battery	2 x 12 V -165 AH
Other Configuration	ABS	Optional
	A/C	√
Cargo box	Length (mm) of the cargo bucket	5600
	Width (mm) the cargo bucket	2300
	Height (mm) the cargo bucket	1500
	Bucket volume (m³)	20
	Bottom Thickness (mm)	8
	Side Thickness (mm)	6
	Lifting type	Front lifting



ACCRA, Graphic Road
Head office
South Industrial Area.
P. O. Box 5216, Accra
Tel: +233 (556) 644 300
+233 (244) 342 430

TEMA,
Cocoa Processing Road
P. O. Box 199, Tema.
Tel: +233 (593) 872 297

KUMASI,
P. O. Box 6015 Kumasi
Prempeh 1 Street Adum.
Tel: +233 (203) 300 762

TAMALE,
P. O. Box TL Tamale,
Kumasi Road.
Tel: +233 (593) 804 355

TAKORADI,
P. O. Box MC 257, Paa
Grant Avenue. Takoradi.
Tel: +233 (554) 391 153