



FOTON

**EMPOWER
YOUR BUSINESS**



EST-M
14 TONS PAY-LOAD



Fuel Economy | Powerful Engine | Excellent Load Carrier

SPECIFICATION | FOTON EST M FLATBED

BASIC INFORMATION	Function	Cargo truck	BRAKE	Service Brake	Dual circuits pneumatic brake	
	Drive Style	4x2		Parking Brake	Energy-accumulating spring air cut-off brake	
	Steering Wheel Position	Left hand		Auxiliary Brake	Engine exhaust brake	
	Platform	EST-M 14 Tons		SUSPENSION	Front Suspension/ Leaf Spring Number	Longitudinal leaf spring with dual acting telescopic shock absorbers , 10 pieces
	Work Conditions	Standard type			Rear Suspension/ Leaf Spring Number	Longitudinal leaf spring, 10+8 pieces
	Vehicle Model	BJ1226VMPHD-1			FRONT AXLE	Front Axle BrakeType
COMPLETE VEHICLE DIMENSION PARAMETERS	Wheelbase (mm)	5150	REAR AXLE	Type		Single reduction(central reduction)
	Long(mm)	8920		Rear Axle Brake Type	Drum brakes	
	Width(mm)	2460	TYRE	Tyre Size	11R22.5	
	Height(mm)	2980		Numbers of Tyres	6+1	
CABIN	Body Type	Flat roof, all welded steel cab,2-points suspension cab, manual cab tilting, adjustable driver's seat(pneumatic seat), seatbelt for driver and co-driver, manual rear-view mirrors and windows, MP3 + radio + USB	STEERING	Type	Hydraulic steering with power assistance	
	Carrying Number	2 seats + 1 bunk		Steering Wheel	Adjustable	
ENGINE	Engine Model	YC6A240-33	FUEL TANK	Type	Aluminum fuel tank with lockable cap	
	Engine Type	Inline six-cylinder, four-stroke, water cooled, turbocharged, intercooled, diesel engine		Capacity	200L	
	Displacement (cc)	7255	ELECTRICAL SYSTEM	Rated Voltage	24V	
	Max Power (kw/ps/rpm)	176/240/2300		Battery	2x12V-135Ah	
	Max Torque (Nm/rpm)	900/1400-1600	OTHER CONFIGURATION	ABS	Optional	
	Engine Brand	YUCHAI		A/C	Optional	
	Emission	Euro II		Air Deflector	Optional	
CLUTCH	Clutch Type	Single, dry type diaphragm spring		Air horn	Optional	
	Plate Diameter(mm)	φ430	CARGO BOX CONFIGURATION	Long(mm) of the cargo bucket	6800	
	Operating System	Hydraulic control with air pressure assistance		Width(mm) the cargo bucket	2300	
GEARBOX	Gearbox Model	8JS105TA		Height(mm) the cargo bucket	600	
	Gearbox Brand	FAST		Bottom Thickness(mm)	3	
	Numbers of Gears	8 Forward and 2 Reverse	Side Thickness(mm)	1.5		
	PTO	Optional				



ACCRA, Graphic Road
Head office
South Industrial Area.
P. O. Box 5216, Accra
Tel: +233 (556) 644 300
+233 (244) 342 430

TEMA,
Cocoa Processing Road
P. O. Box 199, Tema.
Tel: +233 (593) 872 297

KUMASI,
P. O. Box 6015 Kumasi
Prempeh 1 Street Adum.
Tel: +233 (558) 674 194

TAMALE,
P. O. Box TL Tamale,
Kumasi Road.
Tel: +233 (593) 804 355

TAKORADI,
P. O. Box MC 257, Paa
Grant Avenue. Takoradi.
Tel: +233 (554) 391 153