



# THE POWER YOU NEED

THE DURABILITY YOU CAN COUNT ON



**ETX** 6X4  
TIPPER TRUCK



Fuel Economy | Powerful Engine | Excellent Load Carrier

# SPECIFICATION | ETX 20m<sup>3</sup> Tipper truck

<b>BASIC INFORMATION</b>	Function	Tipper truck	<b>SUSPENSION</b>	Front Suspension/ Leaf Spring Number	Longitudinal leaf spring with dual acting telescopic shock absorbers and anti-roll bar,9 pieces	
	Drive Style	6x4		Rear Suspension/ Leaf Spring Number	Longitudinal leaf spring with balance suspension and anti-roll bar, 12 pieces	
	Steering Wheel Position	Left hand		<b>FRONT AXLE</b>	Capacity(kg)	9000
	Platform	ETX			Front Axle Brake Type	Drum brakes
	Vehicle Model	BJ3253DLPJB-1		<b>REAR AXLE</b>	Type	Double reduction(central reduction and hub reduction), tandem axle with differential locks between wheels and axles
<b>COMPLETE VEHICLE DIMENSION PARAMETERS</b>	Wheelbase (mm)	3825+1350	Capacity(kg)		2 x 16000	
	Long(mm)	8500	Gear Ratio		5.73	
	Width(mm)	2500	Rear Axle Brake Type		Drum brakes	
	Height(mm)	3400	<b>TYRE</b>	Tyre Size	13R22.5	
<b>CABIN</b>	Body Type	Flat roof, all welded steel cab,2-points spring suspension cab, manual hydraulic cab tilting, adjustable driver's seat(pneumatic seat), seatbelt for driver and co-driver, manual rear-view mirrors and windows, MP3 + radio + USB		Numbers of Tyres	10+1	
	Carrying Number	3 seats + 1 bunk	<b>STEERING</b>	Type	Hydraulic steering with power assistance	
<b>ENGINE</b>	Engine Model	WD615.34		Steering Wheel	Adjustable	
	Engine Type	Inline six-cylinder, four-stroke, water cooled, turbocharged, intercooled, diesel engine	<b>FUEL TANK</b>	Type	Aluminum fuel tank with lockable cap	
	Displacement (cc)	9726		Capacity	350L	
	Max Power (kw/ps/rpm)	250/340/2200	<b>ELECTRICAL SYSTEM</b>	Rated Voltage	24V	
	Max Torque (Nm/rpm)	1350/(1100-1600)		Battery	2x12V-165Ah	
	Engine Brand	WEI CHAI	<b>OTHER CONFIGURATION</b>	ABS	Optional	
	Emission	Euro II		A/C	Optional	
<b>CLUTCH</b>	Clutch Type	Single, dry type diaphragm spring	<b>CARGO BOX</b>	Length(mm) of the cargo body	5600	
	Plate Diameter(mm)	φ430		Width(mm) the cargo body	2300	
	Operating System	Hydraulic control with air pressure assistance		Height(mm) the cargo body	1500	
<b>GEARBOX</b>	Gearbox Model	RTD11509C(Q)		Bottom Thickness(mm)	8	
	Gearbox Brand	FAST		Side Thickness(mm)	6	
	Numbers of Gears	9 Forward and 1 Reverse		Cargo body type	Rectangle	
	PTO	•		Lifting type	Front lifting	
<b>BRAKE</b>	Service Brake	Dual circuits pneumatic brake				
	Parking Brake	Energy-accumulating spring air cut-off brake				
	Auxiliary Brake	Engine exhaust brake				



**ACCRA**, Graphic Road  
Head office  
South Industrial Area.  
P. O. Box 5216, Accra  
Tel: +233 (244) - 338 393

**ACCRA**, Silver Star Tower  
Ground Floor,  
Airport City, Accra.  
Tel: +233 (302) - 768 849-51

**TEMA**,  
Cocoa Processing Road  
P. O. Box 199, Tema.  
Tel: +233 (243) - 700 751

**KUMASI**,  
P. O. Box 6015 Kumasi  
Prempeh 1 Street Adum.  
Tel: +233 (322) - 030 200

**TAMALE**,  
P. O. Box TL Tamale,  
Kumasi Road.  
Tel: +233 (372) - 022 125

**TAKORADI**,  
P. O. Box MC 257, Paa  
Grant Avenue. Takoradi.  
Tel: +233 (554) - 391 153

[foton.sales@japanmotors.com](mailto:foton.sales@japanmotors.com) | [www.japanmotors.com](http://www.japanmotors.com)  
Genuine spare parts and affordable quality service throughout Ghana